NEW PRODUCT

temperatures. DIN 58345 Kit (optional)

AKS/AKG 337 PHARMACY REFRIGERATOR

This pharmacy refrigerator ensures reliable storage of medicine. The model is equipped with external digital temperature display and fully electronic temperature control that ensures a correct set temperature between +2°C to +8°C. It features; Open door, high/low alarm, and contact for remote alarm, porthole for external monitoring systems and dual ventilators for optimal uniformity in

SPECIFICATIONS

Temperature Range, °C	+2 to +8°C
Uniformity in performance, °C	Solid: 0,9, Glas; 1,9
Refrigerant	R600a
Number of probes	5
Defrost	Yes- automatic
Internal air distribution	Dual Air Stream
Number of compressors	1
Evaporator cover	Yes
Safety thermostat	No
Noise, dBA	41
Energy consumption, kWh/24h	Solid; 0,65, Glass; 0,91
Voltage, V	220 / 240
Frequency, Hz	50
Plug type	Schuko
Gross volume, litres (cu. ft.)	306 (10,80)
Net volume, litres (cu. ft.)	281(9,92)
Inner Height, mm (inches)	1294 (50,94)
Inner Width, mm (inches)	519 (20,43)
Inner Depth, mm (inches)	420 (16,53)



FEATURES

LED light Yes
-
Porthole Yes
Contact for remote alarm Yes
Castors 2 rear
Doors Glass/Solid
Door closure Yes for glass
Door reversibility Yes

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.



VESTFR#STsolutions

A/S Vestfrost
Falkevej 12
DK-6705 Esbjerg Ø
www.vestfrostsolutions.com

PRODUCT

AKS/AKG 337

PHARMACY REFRIGERATOR

STORAGE

Drawers	Optional incl dividers
Drawer material	ABS
Number of drawers (standard)	N/A
Number of drawers (max)	7 + shelf in bottom
Max loading drawers, kg (lbs)	20
Shelfs	Standard
Shelfs material	Polished steel coated with plastic powder
Number of shelfs incl bottom shelf (Standard)	5
Number of shelfs incl bottom shelf (max)	7
Max loading shelfs, kg (lbs)	20

CONTROLLER

Туре	XW737K
USB connection	Yes
Data connection	MODBUS
Languages	3 digits
Logs of data/alarm	35000
High/Low temperature alarm	Yes
Open door alarm	Yes
Probe failure alarm	Yes
Temperature graph	No

OPTIONALS

Chart recorder	No
Drawers	Optional
Dividers for drawers	Standard in drawers
DIN 58345 Kit	Yes

DIMENSIONS AND CONSTRUCTION

Height, mm (inches)	1605 (63,2)
Width, mm (inches)	596 (23,4)
Depth, mm (inches)	602 (23,7)
Depth incl. doorhandle, mm (inches)	655 (25,8)
Gross weight, kg (lbs)	Solid; 75,2 (165,8), Glass; 68 (149,9)
Net weight, kg (lbs)	Solid; 73,4 (161,8), Glass; 79.8 (175,9)
Material inner cabinet	White coated PVC
Material outer cabinet	Prepainted galvanized steel
Insulation thickness	35
Insulation type	Polyurethane with cyclopentane
Type of packaging	Plastic with EPS

Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.





A/S Vestfrost
Falkevej 12
DK-6705 Esbjerg Ø
www.vestfrostsolutions.com

DETAILS

AKS/AKG 337

PHARMACY REFRIGERATOR

- Designed and manufactured by A/S Vestfrost in Denmark
- · Unit optimized for optimal footprint

ENVIRONMENT

- · Eco-friendly R600a refrigerant
- · Efficient cyclopentane insulation
- · Low energy consumption


FEATURES

- · Digital XW737K controller with display
- · Reversable glass door with aluminium handle
- · Top LED light for maximum visibility
- Integrated lock to prevent unauthorized access
- · Open door, high/low, and probe failure alarm
- · Porthole for external monitoring systems

QUALITY

- · User-friendly and maintenance-free
- · Single compressor system
- · Galvanized, pre-painted steel cabinet
- · Dual ventilators
- · Evaporator cover
- · DIN 58345 kit (optional)





Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.





A/S Vestfrost
Falkevej 12
DK-6705 Esbjerg Ø
www.vestfrostsolutions.com